FS4-3J

Flow Switch

The FS4-3J flow switch is a paddle type flow switch to be mounted in 1 to 6 (B) pipe of a water process pipe run, and is used to detect water flow or level for a water cut-off relay.

The flow sensing section is composed of a paddle and bellows that operate a microswitch when the flow changes. The flow rate that operates or stops the switch can be set by an adjustment screw.



Specifications

Body/	Applicable fluid Water (non-corrosive)													
operating unit	Operation & output	ON-OFF (microswitch SPDT contacts)												
	Model No.	Wetted area material		Max. pressure		Temperature range		Mass		r		M		
											Mounting			
	FS4-3J	Body: brass Paddle: monel		1.03MPa	(0 to 150°C		Approx. 1.2kg		(R1 tapped body right in the horizontal pipe run			
	Max. flow speed	2m/s												
	Actuation flow rate	FI	Pipe size (B)	1	1 1/4	1 1/2	2	2 1/2	. 3	3	4	5	6	
	(standard value)	Flow	11.		07	+ 40					150	200		
	Min. adjustment (factory settings)	Actuation	ℓ /min	23	37	48	71		11		150	222	300	
			m/s	0.67	0.64	0.60	0.5			-	0.30	0.28	0.26	
		Stoppage	ℓ /min	14	21	27	36		4	_	75	111	150	
			m/s	0.40	0.36	0.33	0.2				0.15	0.14	0.13	
	Max. adjustment	Actuation	ℓ /min	39	64	87	127				278	435	628	
			m/s	1.17	1.09	1.09	0.9	4 0.82	0.6	68	0.56	0.56	0.55	
		Stoppage	ℓ /min	35	57	74	91	142	17	75	243	348	466	
			m/s	1.03	0.97	0.90	0.8	8 0.75	0.6	60	0.49	0.44	0.41	
	Paddle dimension to use	ISe*		For 1B	32mm	38mm	For 2	2B 57mn	n For	3B	92	117.5	143	
	Contact rating (motor duty)	Voltage		115Vac		230Vac		115Vd	lc	230	Vdc		115 to 230Vac	
		Full load Locked rotor		7.4A 44.4A		3.7A						Pilo	Pilot load	
						22.2A		0.3A		0.	15A	12	125VA	
General	Straight pipe length required for mounting	At least 5 times the pipe diameter is required on both upstream and downstream sides for mounting.												
	Accessories	Paddles: part N	lo. FS4-15SS for 1, 2,	3 and 6B size	s, and part	No. FS-15RP fo	r 1 and 6	B sizes						
	Approval bodies	CSA												

^{*} The paddles are trimmed to match pipe sizes. No trimming is required for 1, 2 or 3B pipe sizes with a tee.

Selection Guide

Model No.	Description					
FS4-3J	Flow switch					

Dimensions (Unit: mm)

